



- GAS SPRING WARNING LABEL MUST NOT BE REMOVED OR OBSCURED
- THE GAS SPRING MUST NOT BE DAMAGED, PUNCTURED OR OPENED
- LINE UP CONNECTIONS PERMISSIBLE DEVIATION +- 5 DEG
- PROTECT SHAFT FROM DEBRIS AND DAMAGE
- PERMISSIBLE OPERATING TEMPRATURE RANGE -40° +300°
- PRODUCT LENGTH TOLERANCE IS +-08 IN (2MM)
- MAXIMUM PISTON SPEED IS APPROXIMATELY 12 IN/SEC.

TOLERANCES/UNLESS
 OTHERWISE SPECIFIED
 X DECIMAL +/- .000
 XX DECIMAL +/- .008
 XXX DECIMAL +/- .005
 ANGULAR +/- 1/2 DEG.

THIS DRAWING IS THE PROPERTY
 OF AMERITool, AND INCORPORATES
 PROTECTIVE AND INDEMNITIES
 PROVISIONS. IT IS TO BE
 DISTRIBUTED IN WHOLE OR IN
 PART ONLY TO THE PERSONS
 AUTHORIZED BY AMERITool. THE
 DRAWING IS NOT TO BE REPRODUCED
 OR TRANSMITTED IN ANY FORM
 OR BY ANY MEANS, ELECTRONIC
 OR MECHANICAL, INCLUDING
 PHOTOCOPYING, RECORDING, OR
 BY ANY INFORMATION STORAGE
 AND RETRIEVAL SYSTEM, WITHOUT
 THE WRITTEN PERMISSION OF
 AMERITool. ALL RIGHTS RESERVED.

AMERITool M.F.G. INC.

316 STAINLESS STEEL GAS SPRINGS

STAINLESS STEEL BRACKET

PART#	BR-234	REVISION	A
DRAWN BY	D.C.	DATE	9/28/11
ONLY FOR INFORMATION		SHEET	1
		OF	1